

World's Smallest and Lightest 6,500lm Project
Enhances Communication in Brightly Lit Spaces

6,500lm	WUXGA	6,000,000:1
---------	-------	-------------



Item	Description	
패널	16.3mm (0.64") (16:10 비율) LCD × 3	
해상도	WUXGA (1,920 x 1,200)	
광 원	Laser diodes (광원수명 - Nomal : 20,000h / Eco : 24,000h)	
밝 기	6,500 Lumens	
명암비	6,000,000:1	
주변조도비	85%	
투사비	Throw Ratio 1.09~2.21:1 (Corresponding value. When used together with optical zoom.)	
스크린 사이즈	0.76-7.62 m [30-300 in], 16:10 aspect ratio	
렌즈	1.6x Manual zoom(throw ratio: 1.09~1.77:1), F = 1.58~1.91, f = 15.3~24.6 mm	
단자	HDMI 1 IN /2 IN	HDMI 19-pin x 2 Deep Color, compatible with HDCP 1.4, 4K/30p signal input, CEC supported
	COMPUTER IN	D-sub 15-pin (female) (RGB/YBPBR/YCBCR)
	AUDIO IN	M3 stereo mini-jack x 1
	AUDIO OUT	M3 stereo mini-jack x 1
	SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection, HDBase-T™ compliant, 100Base-TX, compatible with PLink™ (Class 2), HDCP 1.4, Deep Color, 4K/30p signal input
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2), compatible with 10Base-T/100Base-TX
	USB(VIEWER /WIRELESS/DC OUT)□	USB connector (Type A) x 1 for Memory Viewer function, optional Wireless Module AJ-WM50,
키스톤 보정	수직 : ±25° / 수평 : ±35°	
렌즈쉬프트	수직: 0~+44 %, 수평: ±20 %	
스피커	모노 10W	
소음	Nomal/Eco : 35 dB / Quiet : 25 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	[MAX] 305W (200~240V) [NORMAL] 270W (200~240 V) / [ECO]: 205W (200~240V) [QUIET1]: 235W (200~240V) / [QUIET2]: 200W (200~240V)	
크기(W×H×D)	399 x 133 x 348 mm (with feet at shortest position)	
무게	Approximately 6.9kg	